





Assembly Instructions


SHAFFER ALABASTER WALL SCONCE



Component Checklist

REF	A	B	C	D
PART				
NAME	Wall Plug	Screw	Wall Bracket	Wall Sconce
QTY	2	2	1	1

Putting Me Together



220-240V-50Hz E14 Max.60W

Bulb not included



NOTE: THIS ITEM MUST BE INSTALLED BY A LICENSED ELECTRICIAN

WARNING: Switch off the main electrical supply at the main fuse box / circuit breaker before installation.

- ① Carefully remove all the parts from the box. Remove mounting bracket (C) from the back plate of wall sconce by unscrewing the small screws attached to the side of the wall plate.
- ② **Due to its weight, this wall sconce must be installed to a timber wall stud.**
 - Drill holes into the wall, in line with timber stud, according to the size of mounting bracket screws and in line with holes in mounting bracket (C).
 - Insert ceiling plug (A) into the drilled holes in timber wall stud.
 - Fix mounting bracket (C) to the timber wall stud using screws (B).
- ③ **ENSURE THE ELECTRICITY SUPPLY IS TURNED OFF.**
Connect the 3 power wires from the wall sconce to the power wires in the wall.
 - Brown is the Live wire.
 - Blue is the Neutral wire.
 - Green/Yellow is the Earth wire.
- ④ Secure wall sconce to the mounting bracket by screwing back into place with the knobs onto the front of the mounting bracket.
- ⑤ Remove the alabaster cylinder from the lamp holder by unscrewing it.
- ⑥ Insert E14 globe into the lamp holder, screwing in until firm (globe not included).
- ⑦ Reattached the alabaster cylinder by screwing back on to the lamp holder.
- ⑧ Turn the electricity supply back on and enjoy!