

# **DECO-13-RND-TRIO**



















# Fixed LED Downlight

## Description

The DECO range of LED downlights have been designed with a deep-set frame to reduce glare from the light source. Featuring a wide light distribution, and with an ultra slim housing, allows for this downlight to be suitable for installations where ceiling space is minimal. Complete with a dimmable LED driver and flex and plug. Fully dimmable with

Now with TRIO, the added option of changing the colour temperature output of the downlight with a dip switch at the back of the fitting.







### Specification Features

240V AC Input Voltage: Power (W): 13W 44\* IP rating (IP):

Lumens (lm): Warm White 3000K - 1186lm

Neutral White 4000K - 1306lm White 5700K - 1237lm

LED type: SMD

CCT: 3000K - 4000K - 5700K (Switchable)

CRI: ≥83 90° Beam angle (°): Dimmable: Yes\*\* 50,000hrs Lifespan (hrs): Cutout (Ø): Ø90<sub>mm</sub>

01633D2-CSBMESH


\* IP44 rating is from the underside of the down light once installed into the ceiling.







### Diagrams / Additional



m
n

Item No.		Variant		CCT
	Wht	BLK	Alu	CCT
DECO-13-RND	20420	20421	20422	
		DALI		TRIO
	21588	21589	21590	