

DECO-28-TRIO

















Fixed LED Downlight

Description

The DECO-28 range of commercial LED downlights have been designed with a deep-set frame to reduce glare from the light source. Featuring a wide light distribution, and with an ultra slim housing, allows for this downlight to be suitable for installations where ceiling space is minimal. Complete with a dimmable LED driver and flex and plug. Fully dimmable with suitable dimmers

Now with TRIO, the added option of changing the colour temperature output of the downlight with a dip switch at the back of the fitting.



Specification Features

Input Voltage: 240 V AC
Power (W): 28 W
IP rating (IP): 44*

Lumens (lm): Warm White 3000 K-2300 lm

Neutral White 4000K - 2350lm

White 5700K - 2400lm

LED type: SMD

CCT: 3000K - 4000K - 5700K (Switchable)

CRI: ≥80

Beam angle (°): 90°

Dimmable: Yes**

Lifespan (hrs): 50,000hrs

Lifespan (hrs): 50,000hrs

Cutout (Ø): Ø200-210mm


* 1P44 rating is from the underside of the down light once installed into the ceiling.







Diagrams / Additional



Cutout: Ø200 - Ø210mm

Item No.	Variant		CCT
	Wht	Blk	CCI
DECO-28	20434	20435	
	DALI		TRIO
	21596	21597	

^{**} Fully dimmable with suitable dimmers.