



product specification

www.oriel-lighting.com.au

THETA LED 4000K White

SKU:UA4704WH

Our THETA 4000K recessed LED provides an effective 850lm from a mere 13w of power. Rated at IP44 the Theta can be used in most applications. Theta has excellent colour rendition (Ra80) and a 38 degree beam width. Supplied complete with a 350mA driver. Upgrade to a dimmable driver is also possible. CA90 insulation rating - abutted only.

Additional information



Shipping Weight	0.4 kg
Shipping Carton Dimensions	12.5 × 12.0 × 12.0 cm
Brand	Urban Architectural Lighting
Colour	White
Globe Type	INTEGRAL.LED
Max. Wattage	13W
Voltage	240V
Overall Height	10
Overall Width	11
Overall Depth	11
Fitting Diameter	11
Fitting Cutout	92mm
Fitting Recess	10
Primary Material	METAL
Light Source	SMD LED
Lumen Output	850lm
Colour Temperature	4000K

Colour Rendition (CRI)	>Ra80
IP Rating	IP44
IC Rating	CA90
Supplier Code	UA4704WH
UPI	9324879214100
Electrician To Install	This fitting should be installed by a licenced electrician
Warranty / Guarantee	12 Month Replacement Guarantee

Unless stated, fittings do not include globes (bulbs). No representations are made as to the suitability of this product for your application. All fixed lights (other than DIY lights) should be installed by a licensed electrical contractor. Due to continuing product development, some specifications may change over time. Refer to our detailed Terms and Conditions, online at: www.oriel-lighting.com.au | Details and specifications are current at the time of printing, and with constant product development, subject to change.

(c) Oriel Lighting



quality lighting at affordable prices | specifications subject to change without notice - check the website for the latest information | www.oriel-lighting.com.au